



# Supremium Diesel

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
Issue date: 04.10.2023 Revision date: 29.03.2021 Version: 8.00

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : Supremium Diesel  
Product code : W22910  
Product group : Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Use of the substance/mixture : Diesel fuel additive  
Function or use category : Fuel additives

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier

ITW ADDITIVES INTL B.V.  
Industriepark-West 46  
9100 Sint-Niklaas  
BELGIUM  
T +32 3 766 60 20 - F +32 3 778 16 56  
[msds@wynns.eu](mailto:msds@wynns.eu) - [www.wynns.com](http://www.wynns.com)

##### Distributor

ITW Automotive Aftermarket  
Saxon House, 2-4 Victoria Street  
SL4 1EN Windsor  
UNITED KINGDOM  
T +44 (0)24 7647 2634  
[sales@wynns.uk.com](mailto:sales@wynns.uk.com) - [www.wynns.uk.com](http://www.wynns.uk.com)

##### Distributor

Wynn's Automotive France S.A.S.  
2 Av. Léonard de Vinci Z.A. Europarc  
33600 PESSAC Cedex  
FRANCE  
T +33 5 57 26 29 00  
[contact@wynns.fr](mailto:contact@wynns.fr) - [www.wynns.fr](http://www.wynns.fr)

##### Distributor

Krafft S.L.U.  
Carretera de Urnieta, s/n  
20140 Andoain - Guipúzcoa  
ESPAÑA  
T +34 943 410 400 - F +34 943 410 440  
[msds@krafft.es](mailto:msds@krafft.es) - [www.krafft.es](http://www.krafft.es)

#### 1.4. Emergency telephone number

Emergency number : BIG: +32(0)14 58 45 45 (NL FR EN DE)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (oral), Category 4	H302
Acute toxicity (inhalation:dust,mist) Category 4	H332
Aspiration hazard, Category 1	H304
Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411

Full text of H- and EUH-statements: see section 16

##### Adverse physicochemical, human health and environmental effects

No additional information available

# Supremium Diesel

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

GHS08

GHS09

Signal word (CLP) :

Danger

Contains :

2-Ethylhexyl nitrate; C8-C26 branched and linear hydrocarbons – Distillates; Hydrocarbons, C10, aromatics, <1% naphthalene; 2-ethylhexan-1-ol

Hazard statements (CLP) :

H302+H332 - Harmful if swallowed or if inhaled.

H304 - May be fatal if swallowed and enters airways.

H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) :

P102 - Keep out of reach of children.

P405 - Store locked up.

P261 - Avoid breathing vapours.

P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P331 - Do NOT induce vomiting.

EUH-statements :

EUH044 - Risk of explosion if heated under confinement.

EUH066 - Repeated exposure may cause skin dryness or cracking.

### 2.3. Other hazards

Contains no PBT/vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

Component	
2-ethylhexan-1-ol (104-76-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2-Ethylhexyl nitrate	CAS-No.: 27247-96-7 EC-No.: 248-363-6 REACH-no: 01-2119539586-27	$\geq 50$	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Acute Tox. 4 (Inhalation:dust,mist), H332 (ATE=1,5 mg/l/4h) Aquatic Chronic 2, H411 EUH044 EUH066

# Supremium Diesel

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
C8-C26 branched and linear hydrocarbons – Distillates	CAS-No.: 848301-67-7 EC-No.: 481-740-5 REACH-no: 01-0000020119-75	25 – 50	Asp. Tox. 1, H304 EUH066
Hydrocarbons, C10, aromatics, <1% naphthalene	EC-No.: 918-811-1 REACH-no: 01-2119463583-34	2,5 – 5	STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066
2-ethylhexan-1-ol substance with a Community workplace exposure limit	CAS-No.: 104-76-7 EC-No.: 203-234-3 REACH-no: 01-2119487289-20	2,5 – 5	Acute Tox. 4 (Inhalation:dust,mist), H332 (ATE=1,1 mg/l/4h) Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Check the vital functions. Keep victim at rest in half upright position. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Keep watching the victim. Give psychological aid. Prevent cooling by covering the victim (no warming up). Keep the victim calm, avoid physical strain. If necessary seek medical advice.
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
First-aid measures after skin contact	: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: If swallowed, rinse mouth. Do NOT induce vomiting. Call a POISON CENTER/doctor if you feel unwell. Ingestion of large quantities: immediately to hospital.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after ingestion	: Headache. Abdominal pain. Harmful if swallowed. Risk of aspiration pneumonia. May be fatal if swallowed and enters airways.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. AFFF foam. ABC-powder.
------------------------------	---------------------------------------

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Combustible liquid. Flammable liquid and vapour. Take precautionary measures against static discharge.
Explosion hazard	: Risk of explosion if heated under confinement.

# Supremium Diesel

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 5.3. Advice for firefighters

- Firefighting instructions : Prevent fire fighting water from entering the environment.  
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Use special care to avoid static electric charges. No open flames. No smoking.

#### 6.1.1. For non-emergency personnel

- Protective equipment : Wear suitable gloves and eye/face protection. protective clothing.  
Emergency procedures : Mark the danger area. Keep upwind. Prevent flow to low areas. In confined space use self-contained breathing apparatus. Take off contaminated clothing.

#### 6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

- For containment : Collect spillage. Contain leaking substance, pump over in suitable containers.  
Methods for cleaning up : Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Clean preferably with a detergent - Avoid the use of solvents.

### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Meet the legal requirements. Repeated exposure may cause skin dryness or cracking. Presents no particular risk when handled in accordance with good occupational hygiene practice.  
Hygiene measures : Use good personal hygiene practices. IF ON SKIN: Gently wash with plenty of soap and water. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Does not require any specific or particular technical measures.  
Storage conditions : Meet the legal requirements. Protect from sunlight. Store in a well-ventilated place. Store in a closed container.  
Storage area : Meet the legal requirements. Ventilation along the floor.  
Special rules on packaging : Store in a closed container. Labelling according to.

### 7.3. Specific end use(s)

Read label before use. Observe the label precautions. See product bulletin for detailed information.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

# Supremium Diesel

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>Hydrocarbons, C10, aromatics, &lt;1% naphthalene</b>	
<b>Belgium - Occupational Exposure Limits</b>	
OEL TWA	200 mg/m <sup>3</sup>
<b>2-ethylhexan-1-ol (104-76-7)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
IOEL TWA	5,4 mg/m <sup>3</sup>
IOEL TWA [ppm]	1 ppm
<b>Germany - Occupational Exposure Limits (TRGS 900)</b>	
AGW (OEL TWA) [1]	110 mg/m <sup>3</sup>
AGW (OEL TWA) [2]	20 ppm

### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

<b>2-Ethylhexyl nitrate (27247-96-7)</b>	
<b>DNEL/DMEL (Workers)</b>	
Long-term - systemic effects, dermal	1 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	0,35 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, dermal	0,52 mg/kg bodyweight/day
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	10 mg/l
<b>C8-C26 branched and linear hydrocarbons – Distillates (848301-67-7)</b>	
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	2,06 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	1,68 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	10 mg/l

<b>Hydrocarbons, C10, aromatics, &lt;1% naphthalene</b>	
<b>DNEL/DMEL (Workers)</b>	
Long-term - systemic effects, dermal	12,5 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	151 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, oral	7,5 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	32 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	7,5 mg/kg bodyweight/day

### 8.1.5. Control banding

No additional information available

# Supremium Diesel

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

##### Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Does not require any specific or particular technical measures. Ensure good ventilation of the work station.

#### 8.2.2. Personal protection equipment

##### Personal protective equipment:

Gloves. Safety glasses.

##### Personal protective equipment symbol(s):



##### 8.2.2.1. Eye and face protection

No additional information available

##### 8.2.2.2. Skin protection

##### Hand protection:

Neoprene. Nitrile rubber. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Time of penetration is to be checked with the glove producer

##### 8.2.2.3. Respiratory protection

No additional information available

##### 8.2.2.4. Thermal hazards

No additional information available

#### 8.2.3. Environmental exposure controls

##### Other information:

Breakthrough time : >30'. Thickness of the glove material >0,1 mm.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Yellow.
Appearance	: clear.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 71 °C (ASTM D93)
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: 2,6 mm <sup>2</sup> /s @ 40°C (ASTM D445)
Solubility	: insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 0,9 g/cm <sup>3</sup> @ 20°C (ASTM D4052)
Relative density	: Not available
Relative vapour density at 20°C	: Not available

# Supremium Diesel

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Particle characteristics : Not applicable

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

Additional information : The physical and chemical data in this section are typical values for this product and are not intended as product specifications.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use. Risk of explosion if heated under confinement. Exothermic decomposition.

### 10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep away from strong acids and strong oxidizers.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. On burning: release of harmful/irritant gases/vapours. Carbon monoxide. Carbon dioxide.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Harmful if swallowed.  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Harmful if inhaled.

Supremium Diesel	
ATE CLP (oral)	909,753 mg/kg bodyweight
ATE CLP (dust,mist)	2,515 mg/l/4h
2-Ethylhexyl nitrate (27247-96-7)	
LD50 oral rat	> 9600 mg/kg bodyweight Sprague-Dawley
C8-C26 branched and linear hydrocarbons – Distillates (848301-67-7)	
LD50 oral rat	> 5000 mg/kg bodyweight Sprague-Dawley
LD50 dermal rat	> 2000 mg/kg bodyweight Sprague-Dawley
Hydrocarbons, C10, aromatics, <1% naphthalene	
LD50 oral rat	6318 mg/kg bodyweight CrI:CDBR
LD50 dermal rabbit	> 2000 mg/kg bodyweight New Zealand White

# Supremium Diesel

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hydrocarbons, C10, aromatics, <1% naphthalene	
LC50 Inhalation - Rat	> 4,688 mg/l/4h Sprague-Dawley

2-ethylhexan-1-ol (104-76-7)	
LD50 oral rat	2047 mg/kg
LD50 dermal rabbit	> 3000 mg/kg
LC50 Inhalation - Rat	1,1 mg/l/4h

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified

Hydrocarbons, C10, aromatics, <1% naphthalene	
STOT-single exposure	May cause drowsiness or dizziness.

2-ethylhexan-1-ol (104-76-7)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.

Supremium Diesel	
Viscosity, kinematic	2,6 mm <sup>2</sup> /s @ 40°C (ASTM D445)

2-Ethylhexyl nitrate (27247-96-7)	
Viscosity, kinematic	1,767 mm <sup>2</sup> /s

C8-C26 branched and linear hydrocarbons – Distillates (848301-67-7)	
Viscosity, kinematic	2 – 4,5 mm <sup>2</sup> /s

Hydrocarbons, C10, aromatics, <1% naphthalene	
Viscosity, kinematic	< 2 mm <sup>2</sup> /s
Aliphatic, alicyclic or aromatic hydrocarbon	Yes

### 11.2. Information on other hazards

No additional information available

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: This product contains hazardous components for the aquatic environment.
Ecology - water	: Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.

2-Ethylhexyl nitrate (27247-96-7)	
LC50 - Fish [1]	96h 2 mg/l Brachydanio rerio
EC50 - Crustacea [1]	> 12,6 mg/l @48h Daphnia magna



# Supremium Diesel

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>2-Ethylhexyl nitrate (27247-96-7)</b>	
EC50 - Other aquatic organisms [1]	72h 1,57 mg/l Pseudokirchnerella subcapitata
<b>C8-C26 branched and linear hydrocarbons – Distillates (848301-67-7)</b>	
LC50 - Fish [1]	> 1000 mg/l @96h Pimephales promelas
EC50 - Crustacea [1]	> 1000 mg/l @48h Daphnia magna
EC50 - Other aquatic organisms [1]	> 1000 mg/l @72h Pseudokirchneriella subcapitata
NOEC (acute)	> 1000 mg/l @48h Daphnia magna
<b>Hydrocarbons, C10, aromatics, &lt;1% naphthalene</b>	
LC50 - Fish [1]	96h 2 (≤ 5) mg/l Oncorhynchus mykiss
EC50 - Crustacea [1]	48h 3 (≤ 10) mg/l Daphnia magna
EC50 - Other aquatic organisms [1]	72h 1 (≤ 3) mg/l Pseudokirchneriella subcapitata
NOEC chronic fish	0,441 mg/l
NOEC chronic crustacea	0,771 mg/l
NOEC chronic algae	1 mg/l
<b>2-ethylhexan-1-ol (104-76-7)</b>	
LC50 - Fish [1]	96h 28,2 mg/l pimephales promelas
EC50 - Crustacea [1]	48h 39 mg/l daphnia magna
EC50 - Other aquatic organisms [1]	72h 11,5 mg/l algae (desmodesmus subspicatus)
<b>12.2. Persistence and degradability</b>	
<b>2-Ethylhexyl nitrate (27247-96-7)</b>	
Persistence and degradability	Not readily biodegradable.
<b>C8-C26 branched and linear hydrocarbons – Distillates (848301-67-7)</b>	
Persistence and degradability	Readily biodegradable.
<b>Hydrocarbons, C10, aromatics, &lt;1% naphthalene</b>	
Persistence and degradability	Readily biodegradable.
Biodegradation	50 %
<b>2-ethylhexan-1-ol (104-76-7)</b>	
Persistence and degradability	Readily biodegradable.
<b>12.3. Bioaccumulative potential</b>	
<b>C8-C26 branched and linear hydrocarbons – Distillates (848301-67-7)</b>	
Partition coefficient n-octanol/water (Log Pow)	> 6,5 @40°C
<b>2-ethylhexan-1-ol (104-76-7)</b>	
Bioaccumulative potential	No bioaccumulation.

## 12.4. Mobility in soil

No additional information available

# Supremium Diesel

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 12.5. Results of PBT and vPvB assessment

#### Component

2-ethylhexan-1-ol (104-76-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
------------------------------	---

### 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

No additional information available





## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Remove to an authorized waste treatment plant. Avoid release to the environment.
European List of Waste (LoW) code	: 14 06 03* - other solvents and solvent mixtures 15 01 10* - packaging containing residues of or contaminated by dangerous substances

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number or ID number</b>				
UN 3082	UN 3082	UN 3082	Not applicable	UN 3082
<b>14.2. UN proper shipping name</b>				
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-Ethylhexyl nitrate)	(2-Ethylhexyl nitrate)	(2-Ethylhexyl nitrate)	Not applicable	(2-Ethylhexyl nitrate)
<b>Transport document description</b>				
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-Ethylhexyl nitrate), 9, III	UN 3082 (2-Ethylhexyl nitrate), 9, III, MARINE POLLUTANT	UN 3082 (2-Ethylhexyl nitrate), 9	Not applicable	UN 3082 (2-Ethylhexyl nitrate), 9
<b>14.3. Transport hazard class(es)</b>				
9	9	9	Not applicable	9
			Not applicable	
<b>14.4. Packing group</b>				
III	III	Not applicable	Not applicable	Not applicable

# Supremium Diesel

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
<b>14.5. Environmental hazards</b>				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Not applicable	Dangerous for the environment: Yes
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR) : M6  
Special provisions (ADR) : 274, 335, 375, 601  
Limited quantities (ADR) : 5I  
Excepted quantities (ADR) : E1  
Vehicle for tank carriage : AT  
Transport category (ADR) : 3  
Hazard identification number (Kemler No.) : 90  
Orange plates :



EAC code : •3Z

#### Transport by sea

No data available

#### Air transport

No data available

#### Inland waterway transport

Not applicable

#### Rail transport

No data available

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

##### REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

##### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

##### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

##### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

##### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

##### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

# Supremium Diesel

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

### Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

### 15.1.2. National regulations

#### France

Occupational diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

#### Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).  
Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

#### Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed  
SZW-lijst van mutagene stoffen : None of the components are listed  
SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed  
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed  
SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

#### Denmark

Class for fire hazard : Class III-1  
Store unit : 50 liter  
Classification remarks : Flammable according to the Danish Ministry of Justice; Emergency management guidelines for the storage of flammable liquids must be followed  
Danish National Regulations : Young people below the age of 18 years are not allowed to use the product  
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

### 15.2. Chemical safety assessment

No additional information available

## SECTION 16: Other information

### Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
EUH044	Risk of explosion if heated under confinement.
EUH066	Repeated exposure may cause skin dryness or cracking.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H302	Harmful if swallowed.

# Supremium Diesel

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.